



INTRODUCING THE NEW

14GT

TELESCOPIC
GOOSENECK DUMP

The all-new Big Tex 14GT provides rock-solid carrying performance for equipment and debris haulers in the construction and landscaping business. This heavy-duty gooseneck trailer offers a 12-ton, 3-stage telescopic hydraulic cylinder that provides superior lift capacity for any load. The telescopic cylinder also makes for smoother lifts, too. Loaded with a feature-rich dump box complete with an integrated crank-style tarp shroud and tarp, D-ring tie downs, and a rear combo gate – and the 14GT is built for heavy hauling users.






BigTex
TRAILERS®

www.bigtextrailers.com/14GT

14GT | HEAVY DUTY TELESCOPIC GOOSENECK DUMP

BigTex
TRAILERS®

www.bigtextrailers.com/14GT

 GVWR: 15,900#
  EMPTY WEIGHT: 5,110# (16')
  LENGTH: 14', 16'
  BED WIDTH: 83" WIDE
  COUPLER: 2-5/16" Round Adj. Pin (25K)



TELESCOPIC CYLINDER HOIST

The 12-ton cylinder creates more leverage for a smoother, more efficient lift - and less worry about leveling the load.



HEAVY DUTY FRAME DESIGN






For the ultimate in strength and durability, the 14GT features an 8" I-beam frame with 10" I-beam neck. This frame design will stand the test of time and have no issues supporting the 15,900# GVWR of the 14GT.



STRENGTH & VERSATILITY

The 14GT is equipped with a 3"x2" rectangular tubing structural top rail for added strength and durability as well as stakepockets along the sides for added cargo control and to support after-market side extensions.

14GT | HEAVY DUTY TELESCOPIC GOOSENECK DUMP

 GVWR: 15,900#
  EMPTY WEIGHT: 5,110# (16')
  LENGTH: 14', 16'
  BED WIDTH: 83" WIDE
  COUPLER: 2-5/16" Round Adj. Pin (25K)



www.bigtextrailers.com/14GT

SPECIFICATIONS

G.V.W.R.	15,900#
G.A.W.R. (Ea. Axle)	7,000#
HYDRAULICS	12 Ton 3-Stage Telescopic Cylinder
COUPLER	2-5/16" Round Adjustable Pin Gooseneck (25K)
SAFETY CHAINS	3/8" Grd. 70 w/Safety Latch Hook (2 each)
JACK	Dual 12,000# Drop Leg Side Wind
NECK	10" I-Beam Neck
MAIN FRAME	8" I-Beam Frame, 13#
DUMP BODY CRMS	3" Channel, 16" Centers
DUMP BODY SIDES	24" Tall Sides (10 Gauge)
DUMP BODY TOP RAIL	3" x 2" Rectangular Tubing
FENDERS	9" x 72" 14 Ga. Diamond Plate Double Square Broke
AXLE	(2) 7,000# Axles w/Quick Lubricating Hubs & Elec. Brakes
SUSPENSION	Multi-Leaf Spring w/Equalizer
TIRE	ST235/80 R-16 Load Range E
WHEEL	16" x 6"; Black Mod, 8 Bolt
FLOOR	10 Gauge Smooth Steel
LIGHTS	L.E.D. D.O.T Stop, Tail, Turn & Clearance
ELEC. PLUG	7-Way RV

WEIGHTS & CAPACITIES

Length	Empty Weight	Payload	Box Capacity
14'	4,650#	11,250#	7.2 Cubic Yards
16'	5,110#	10,790#	8.3 Cubic Yards

OPTIONAL EQUIPMENT

Category	Code	Description
AXLES	DRPAX	Drop Axles (Lowers Deck Height to 24" from Ground)
JACKS	D2SPJ*	Dual 2-Speed Landing Gear
TIRE/WHEEL	SP	Spare Tire (ST235/80 R-16 LR-E)
TIRE/WHEEL	TU	Tire Upgrade (ST235/80 R-16 LR-G)
TIRE/WHEEL	SPU	Spare Tire Upgrade (ST235/80 R-16 LR-G)
RAMPS	6SIR	6.5' Slide In Ramp Package
POWER	WRMT	Wireless Remote
POWER	5WCH	5 Watt Solar Charger
BODY	7GA	Upgrade Floor to 7-Gauge Steel
BODY	P3	3' Solid Sheet Metal Sides
BODY	P4	4' Solid Sheet Metal Sides
BODY	RDON*	Removable Deck on Neck- Bolt On (8' x 6')

* Selecting this Option(s) will move unit to Specialty Manufacturing Line potentially causing extended lead times

DIMENSIONS

Bed Length	A	B	C
14GT-14	168"	100"	68"
14GT-16	192"	115 3/4"	76 1/4"

