

THE NEW

20GX

MEGA DUTY TANDEM AXLE
GOOSENECK DUMP



BigTex
TRAILERS®

www.bigtextrailers.com/20GX

The new 20GX dump trailer provides the muscle to handle hefty loads, with capable 10,000# torsion axles equipped with Super Single Wheels. A heavy-duty dump box is equipped with a 7-gauge steel floor and 3' high sides for added cubic capacity. Unlike most dump trailers in this weight class, the 20GX boasts a user-friendly low-profile dump bed, making loading and unloading heavy equipment quick and easy when combined with the optional slide-in ramp package. Add to that the efficient scissor hoist, standard tarp kit and durable I-Beam frame, and the 20GX is ready to take on anything you throw at it.

20GX | MEGA DUTY TANDEM AXLE GOOSENECK DUMP

BigTex
TRAILERS®

www.bigtextrailers.com/20GX

GVWR: 22,000#  EMPTY WEIGHT: 6,550#  LENGTH: 16'  BED WIDTH: 82.5" Wide  COUPLER: 2-5/16" Round Adj. Pin (25K)



LOW-PROFILE DECK CLEARANCE

A 30" deck clearance makes loading debris and heavy equipment into this 22,000# GVWR trailer a cinch.



TORSION AXLES AND SUPER SINGLE WHEELS

Capable 10,000# Torsion Axles with Super Single 17.5 Wheels provide heavy-duty cargo capacity while still allowing a low-profile frame design.



OPTIONAL RAMP PACKAGE

Loading and unloading equipment is effortless, thanks to the optional 6.5' Slide-in Ramp package.

20GX | MEGA DUTY TANDEM AXLE GOOSENECK DUMP

 GVWR: 22,000#
  EMPTY WEIGHT: 6,550#
  LENGTH: 16'
  BED WIDTH: 82.5" Wide
  COUPLER: 2-5/16" Round Adj. Pin (25K)

BigTex
TRAILERS®

www.bigtextrailers.com/20GX

SPECIFICATIONS

G.V.W.R.	22,000#
G.A.W.R. (Ea. Axle)	10,000#
COUPLER	2-5/16" Round Adj. Pin (25K)
SAFETY CHAINS	3/8" Grd. 70 w/Safety Latch Hook (2 each)
JACK	Dual 12,000# Drop-Leg Side Wind
NECK	10" I-Beam
MAIN FRAME	10" I-Beam, 19#
DUMP BODY CRMS	3" Channel, 16" Centers
DUMP BODY SIDES	36" Tall Sides (10 Gauge)
DUMP BODY TOP RAIL	3" x 2" Rectangular Tubing
FENDERS	9" x 72" 14-Ga. Diamond Plate Double Square Broke
AXLE	(2) 10,000# Oil Bath w/Electric Brakes
SUSPENSION	Torsion Axles
TIRE	ST235/75 R-17.5 Load Range J
WHEEL	17.5" x 6.75"; Black Mod, 8 Bolt
FLOOR	7-Gauge Smooth Steel
LIGHTS	L.E.D. D.O.T Stop, Tail, Turn & Clearance
ELEC. PLUG	7-Way RV

WEIGHTS & CAPACITIES

Length	Empty Weight	Payload	Box Capacity
16'	6,550#	15,450#	8.3 Cubic Yards

OPTIONAL EQUIPMENT

Category	Code	Description
JACKS	D2SPJ*	Dual 2-Speed Landing Gear
JACKS	DHYDJ*	Dual Elec/Hyd 12,000# by Stillwell™
RAMPS	6SIR	6.5' Slide-In Ramp Package
POWER	WRMT	Wireless Remote
POWER	5WCH	5 Watt Solar Charger
BODY	P4	4' Solid Sheet Metal Sides
BODY	RDON*	Removable Deck on the Neck - Bolt On (8' W x 6' L)

*Selecting this Option(s) will move unit to Specialty Manufacturing Line potentially causing extended lead times

DIMENSIONS

Bed Length	A	B	C
16'	192"	115-1/4"	76-3/4"

